



Semi-Automatic Hydraulic Swivel Head Mitering SH-650M

The swivel sawhead allows the user to lock and cut at any angle up to 60°. The precision pivot system facilitates easy and accurate adjustment for angle cuts. Cosen's SH-650M utilize a protractor and pointer in clear view and away from any chips covering the numbers

ITEMS	COSEN SH-650M		
Angle	0°	+45°	+60°
Capacity Round	420 mm (16.5")	400 mm (16")	250 mm (10")
Capacity Rectangle (HxW)	380x650mm (15"x25.6")	400x400mm (16"x16")	400x250mm (16"x10")
Blade Speed	20-100 m/min (66-330fpm)		
Blade Size (LxWxT)	5300 x 34 x 1.1 mm (209"x 1.3"x 0.042")		
Blade Motor	5 HP (3.75 kW)		
Hydraulic Motor	1 HP (0.75 kW)		
Coolant Motor	1/8 HP (0.09 kW)		
Vise Control method	Hydraulic Full Stroke Cylinder		
Workbed Height	750 mm (29.5")		
Gross Weight	1800 kgs (3960 lbs)		
Floor Space (LxWxH)	2300 x 2900 x 2500 (90.6" x 114" x 98.4")		

*We reserve the right to modify the specification and design of machine without prior notice.

Equipment

1. Adjustable material stop	OPTIONAL: Hydraulic Chip Conveyor
2. Adjustable work light	OPTIONAL: Vise Pressure regulator
3. Additional flushing hose for cleaning	OPTIONAL: Full capacity hydraulic top clamps
4. Bi-metal saw blade	OPTIONAL: 2M Roller Table
5. Tool Box with tools, leveling pads, and an additional wire brush	